

BRIGGS® FAUCETS

B471/ B471BN

SINGLE HANDLE LAVATORY
CERAMIC CARTRIDGE, LOW-LEAD WATERWAY

FEATURES

- Available finishes and style allow this faucet to accommodate most lavatories
- Installation description is single hole
- B471 series includes 50/50 pop-up drain
- Flow is limited to 2.2 gpm max at 60 psi
- Single handle is easy to use and ADA compliant
- Ceramic disc cartridge
 - Non-metallic, non-ferrous and brass materials
 - Single body construction
- One year limited warranty against defects in materials and manufacturing workmanship

FINISHES



CHROME



BRUSHED
NICKEL

MAINTENANCE

Please read the following before installation and operation.

1 Installation

- Rinse the inlet pipe clean.
- Connect the appropriate water supplies:
 - Hot water on the left side
 - Cold water on the right side

2 Technical Parameter

- Water Pressure: 0.1 MPa - 0.86 MPa
- Water Temperature: 41-160° F

3 Surface Maintenance


Remove as much surface dirt and film using clean water and cotton cloth.

Spray cleaners including mild liquid detergents, clear liquid glass cleaner, non-acidic and full dissolved powder cleaners or non-abrasive liquid polishers on a rag are acceptable to clean the faucet surface.


Once clean, rinse the faucet thoroughly with clean water to remove the cleaner then dry with soft cotton cloth.

CODES

- Certified to ASME A112.18.1 IAPMO cUPC



SPECIFICATIONS



■ For reference only (unit = inch)
Illustrations may not be to scale
Dimensions are subject to change
without notice